
NORMETTA®

Banding Systems – Plain Band



Continuous band available in smooth version or with thread stamping throughout

4 different closure types to suit a huge variety of applications



Continuous band clamping system

Consisting of a continuous band, the NORMAFIX® NORMETTA® system is able to adapt itself to the shape and size of various objects. 5 different types of closure are available to choose from. The system is particularly suitable for carrying out retaining and repair work under difficult and extreme conditions.

Advantages at a glance

- Flexible and versatile
- Can be installed under difficult conditions



Applications

- Irrigation systems
- Railway industry
- Building machines
- Pump and filter
- Retaining applications; sealing pipes during repair work
 - Attaching signs and containers
- Binding hoses

Product and closure types

The continuous band is available in a 30 m roll and as either a smooth version with a range of band widths or a version with thread stamping throughout (with 12 mm band width only). It can also be supplied in different material grades.

MaterialsW1W2W3W4W5XXXX

VORMAFIX®

NORMETTA® – Versions

Smooth band



To be used with the buckles NB-A W1, NB-D W4 and NB-H W4.

NORMAFIX® NORMETTA SMOOTH BAND						
Width	Thickness	Designation	Length in m	W1 Product No.	W4 Product No.	
5	0.35	NORMETTA SMOOTH BAND 30M/5 W1	30	0560 8500 004		
9	0.44	NORMETTA SMOOTH BAND 30M/9 W1	30	0560 8500 001		
	0.5	NORMETTA SMOOTH BAND 30M/9 W4	30		0560 5000 009	
13	0.7	NORMETTA SMOOTH BAND 30M/13 W4	30		0560 5000 013	
16	0.7	NORMETTA SMOOTH BAND 30M/16 W4	30		0560 5000 016	
19	0.7	NORMETTA SMOOTH BAND 30M/19 W4	30		0560 5000 019	



Refer to pages 180 and 189.

Stamped band To be used with the buckles NB-G W1 and W3 $\,$ NORMAFIX® NORMETTA STAMPED BAND Resistance Length to traction W1 W3 Width Thickness in N Designation **Product No. Product No.** in m 0.8 NORMETTA STAMPED BAND 30M/12 W1 0560 8566 001 12 30 1700 N 2600 N 0560 8566 003 0.8 NORMETTA STAMPED BAND 30M/12 W3 30 Refer to page 189.

Perforated Band



To be used with buckles NB-K W2.

NORMAFIX [®] NORMETTA PERFORATED BAND						
Width	Thickness	Designation	Length in m	Resistance to traction in N	W2 Product No.	W4 Product No.
8	0.6	NORMETTA PERFORATED BAND 25M/8 W2	25	790 N	0817 7020 001	
0	0.6	NORMETTA PERFORATED BAND 25M/8 W4	25	790 N		0817 7022 001
13	0.6	NORMETTA PERFORATED BAND 25M/13 W4	25	850 N		0817 7022 002
14	0.6	NORMETTA PERFORATED BAND 25M/14 W2	25	850 N	0817 7020 002	



NORMETTA® – Closure types

Banding Systems – Plain Band

NB-A



Closure type NB-A

Suitable for less demanding applications such as attaching signs and sealing low-pressure hoses. Can be re-used.

For bands: 5, 9 mm

Required tools: Steel pin, angled screwdriver or pliers, plate shears

NORMAFIX® NB-A					
For Band width	Designation	W1 Product No.			
5	NB-A5	0560 8520 002			
9	NB-A9	0560 8520 000			



NB-D

NB-G



Closure type NB-D

Suitable for attaching signs and containers to pipes and hoses as well as binding hoses. For bands: 9, 13, 16, 19 mm Required tools: Clamping and cutting tool; hammer

NORMAFIX® NB-D					
For Band width	Designation	W4 Product No.			
9	NB-D/9	0560 8550 009			
13	NB-D/13	0560 8550 013			
16	NB-D/16	0560 8550 016			
19	NB-D/19	0560 8550 019			



Closure type NB-G

Suitable for applications with cramped installation conditions. Can be re-used.

For stamped bands.

Required tools: Screwdriver or SW7 socket wrench and plate shears

NORMAFIX® NB-G

For Band width	Designation	W1 Product No.	W3 Product No.		
12	NB-G/12	0560 8565 001			
12	NB-G/12		0560 8565 003		



NORMETTA® – Closure types

Banding Systems – Plain Band



NB-K

Closure type NB-H

An adjustable quick-release closure that enables fast and easy installation and removal. Can be re-used. For bands:16, 19 mm Required tools: Screwdriver and plate shears

NORMAFIX® NB-H						
For Band width	Maximum diameter in mm	Designation	W1 Product No.			
	124	NB-H/124	0560 8558 124			
16 / 19	400	NB-H/400	0560 8558 400			
	800	NB-H/800	0560 8558 800			



Closure type NB-K

Suitable for fixing suspended ventilation tubes. For bands: 8, 13, 14 mm Required tools: Screwdriver

NORMAFIX® NB-K					
For Band width	Designation	W2 Product No.	W4 Product No.		
8	NB-K/8	0817 7019 003	0817 7021 003		
13	NB-K/13		0817 7021 004		
14	NB-K/14	0817 7019 004			

Refer to page 189.

www.normagroup.com